

Single-Mode Beam Shaping Fiber Lasers

Programmable beam technology to maximize Additive Manufacturing productivity



The nLIGHT® Corona™ AFX fiber laser family provides the ability to switch between a single-mode beam for high-spatial-resolution printing and larger ring beams for greatly accelerated build rates delivering revolutionary productivity with generous process windows and improved material quality.

Features

- **Up to 1.5 kW**
Delivers industry-leading print productivity for large layer thicknesses with improved process stability and reduced soot and spatter, leading to faster printing at lower costs.
- **Optimized Tuning of Beam Size and Shape**
Maintains fiber laser performance, stability, efficiency, and reliability through seven beam shapes from single-mode to large donut.
- **Rapid Beam Switching**
Beam adjustments in less than 30 ms enables real-time optimization of each process step while maintaining full-power operation.
- **Back-Reflection Protection**
Hardware-based back-reflection protection allows processing of even the most reflective metals with no build interruptions or damage to the laser.
- **Innovative All-Fiber Beam Shaping**
All-fiber technology does not use complex, performance-limiting hardware such as free-space optics, zoom process heads, and external fiber-to-fiber couplers.
- **Unparalleled Serviceability**
Durable design ensures continuous operation in manufacturing environments with easy onsite serviceability to maximize uptime.

nLIGHT








nLIGHT AFX Corona Fiber Laser Specifications

Model	AFX-1000	AFX-1500
Optical		
Mode of Operation	CW/Modulated	
Maximum Power, SM Setting	1200 W	1200 W
Maximum Power, MM Settings	1200 W	1500 W
0.10 NA Power Enclosure	> 90%	
Power Tunability	5 to 100%	
Power Variation, 8-Hour	≤ 1%	
Modulation Frequency	≤ 100 kHz	
Rise and Fall Times	≤ 5 μs	
Beam Profile Switching Time	< 30 ms	
Beam Diameter	Programmable (see table below)	
Wavelength	1070 ± 10 nm	
Electrical		
Supply Voltage	200 to 240 VAC, single phase, 50/60 Hz	
Control Interface	External hardware control / RS-232 / Ethernet	
Mechanical		
Dimensions (W x D x H)	445 x 677 x 177 mm	
Optical Fiber ¹	5 or 10 m fiber with QBH connector	
Cooling Method	Water	
Environmental		
Operating Temperature ²	10 to 40 °C	
Storage Temperature	-10 to 60 °C	
Relative Humidity	10 to 80%	

¹ Configuration dependent

² Non-condensing or with use of CDA

nLIGHT AFX Corona Example Beam Characteristics

Index Setting	0	1	2	3	4	5	6
Beam Shape (typical near-field profile)							
Power Ratio (nominal single-mode / ring)	5 / 95	25 / 75	35 / 65	50 / 50	65 / 35	80 / 20	90 / 10
Beam Diameter ³ (nominal near-field)	16 μm	25 μm	30 μm	35 μm	40 μm	43 μm	47 μm

³ Measured using second-moment method

nLIGHT continually improves its products to provide customers outstanding quality and reliability. The information contained herein is subject to change without notice. nLIGHT, Inc. shall not be liable for technical or editorial errors or omissions contained herein. Warranties are set forth in express warranty statements accompanying products. Nothing herein should be construed as constituting an additional warranty. For details, please contact your nLIGHT sales representative.

sales@nlight.net | www.nlight.net

© Copyright 2023 nLIGHT, Inc.

